

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W22Xdb Flameproof - Standard Efficiency IE1 Multivoltage Product code : 17050814

Frame	: 200M/L	Cooling method	: TEFC-XP
Insulation class	: F	Mounting	: B3T
Duty cycle	: S1	Direct of rotation ¹	: Both
Ambient temperature	: -20 °C to +40 °C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l	Approx. weight ³	: 338 kg
Degree of protection	: IP56	Moment of inertia (J)	: 0.1526 kgm ²
Design	: N		

Output	30 kW (40 HP)	30 kW (40 HP)	30 kW (40 HP)	30 kW (40 HP)
Poles	2	2	2	2
Frequency	50 Hz	50 Hz	50 Hz	60 Hz
Rated voltage	380/660 V	400/690 V	415 V	460 V
Rated current	56.8/32.7 A	54.3/31.5 A	52.9 A	47.1 A
L. R. Amperes	369/213 A	375/217 A	381 A	382 A
LRC (p.u.)	6.5	6.9	7.2	8.1 x Code J
No load current	15.0/8.64 A	15.5/8.99 A	17.0 A	15.5 A
Rated speed	2955 rpm	2960 rpm	2965 rpm	3565 rpm
Slip	1.50 %	1.33 %	1.17 %	0.97 %
Rated torque	9.89 kgfm	9.87 kgfm	9.85 kgfm	8.20 kgfm
Locked rotor torque	230 %	260 %	280 %	310 %
Breakdown torque	240 %	270 %	290 %	300 %
Service factor	1.00	1.00	1.00	1.15
Noise level ²	72.0 dB(A)	72.0 dB(A)	72.0 dB(A)	76.0 dB(A)
Locked rotor time	18 s (hot) 32 s (cold)	18 s (hot) 32 s (cold)	18 s (hot) 32 s (cold)	18 s (hot) 32 s (cold)
Efficiency (%)	50%	91.8	91.6	91.3
	75%	91.9	92.0	92.0
	100%	91.2	91.6	91.8
Power factor	Start	0.44	0.44	0.41
	50%	0.80	0.76	0.72
	75%	0.86	0.84	0.81
	100%	0.88	0.87	0.86

	Drive end	Non drive end
Bearing type	6312-C3	6212-C3
Lubrication interval	15000 h	18000 h
Lubricant amount	21 g	13 g
Lubricant type	MOBIL POLYREX EM	

Foundation loads	
Maximum traction	: 191 kgf
Maximum compression	: 529 kgf

CERTIFIED
WEG MOTORES
Certified document.
Not subject to changes.

This revision replaces and cancels the previous one, which must be eliminated.

- (1) When viewed from the drive end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At the rated point.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in IEC 60034-1.

Rev.	Summary of changes	Performed	Checked	Date
Date	10/01/2023		005055/2023	
			Page	Revision
			1/2	0

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization.

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W22Xdb Flameproof - Standard Efficiency IE1 Multivoltage Product code : 17050814

Thermal protection

ID	Application	Type	Quantity	Switching temperature
01	Winding	Thermistor - 2 Wires	1 x Phase	150 °C

Space heater information

Voltage: 200-240 V

Output: 32-46 W

**CERTIFIED
WEG MOTORES**

Certified document.
Not subject to changes.

Standards	Specification : IEC 60034-1	Vibration : IEC 60034-14
	Tests : IEC 60034-2	Tolerance : IEC 60034-1
	Noise : IEC 60034-9	

Rev.	Summary of changes	Performed	Checked	Date
Performed by	e-manumathew	005055/2023		
Checked by	AUTOMATICO	Page Revision		
Date	10/01/2023	2/2 0		

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization.