

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer		:ROSHD SANAT NIROO			
Product line		: W22 IE1 Three-Phase		Product code :	11360626
Frame	:	160M	Locked rotor time	:	16s (cold) 9s (hot)
Output	:	11 kW	Temperature rise	:	80 K
Poles	:	4	Duty cycle	:	S1
Frequency	:	50 Hz	Ambient temperature	:	-20°C to +40°C
Rated voltage	:	380/660 V	Altitude	:	1000 m.a.s.l.
Rated current	:	22.7/13.1 A	Protection degree	:	IP55
L. R. Amperes	:	136/78.4 A	Cooling method	:	IC411 - TEFC
LRC	:	6.0	Mounting	:	B3T
No load current	:	7.90/4.55 A	Rotation ¹	:	Both (CW and CCW)
Rated speed	:	1455 rpm	Noise level ²	:	61.0 dB(A)
Slip	:	3.00 %	Starting method	:	Direct On Line
Rated torque	:	7.36 kgfm	Approx. weight ³	:	111 kg
Locked rotor torque	:	190 %			
Breakdown torque	:	220 %			
Insulation class	:	F			
Service factor	:	1.00			
Moment of inertia (J)	:	0.0906 kgm²			
Design	:	N			
Output	50%	75%	100%	Foundation loads	
Efficiency (%)	87.8	88.2	87.6	Max. traction	: 211 kgf
Power Factor	0.69	0.80	0.84	Max. compression	: 323 kgf
		<u>Drive end</u>	<u>Non drive end</u>		
Bearing type	:	6309 C3	6209 Z C3		
Sealing	:	V'Ring	V'Ring		
Lubrication interval	:	20000 h	20000 h		
Lubricant amount	:	13 g	9 g		
Lubricant type	:	Mobil Polyrex EM			
Notes					

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 4Revision	
Checked by					
Date	21/11/2018				

TORQUE AND CURRENT VS SPEED CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IE1 Three-Phase

Product code : 11360626



Performance : 380/660 V 50 Hz 4P

Rated current : 22.7/13.1 A
LRC : 6.0
Rated torque : 7.36 kgfm
Locked rotor torque : 190 %
Breakdown torque : 220 %
Rated speed : 1455 rpm

Moment of inertia (J) : 0.0906 kgm²
Duty cycle : S1
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : N

Locked rotor time : 16s (cold) 9s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 4Revision		
Checked by				
Date	21/11/2018			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IE1 Three-Phase

Product code : 11360626




Performance : 380/660 V 50 Hz 4P


Rated current : 22.7/13.1 A
 LRC : 6.0
 Rated torque : 7.36 kgfm
 Locked rotor torque : 190 %
 Breakdown torque : 220 %
 Rated speed : 1455 rpm

Moment of inertia (J) : 0.0906 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N


Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				4 / 4	
Date					



Color RAL 5009
Painting plan 203A
Mounting B3T



11 kW 04 Poles 50 Hz A

ECM	LOC	SUMMARY OF MODIFICATIONS				EXECUTED	CHECKED	RELEASED	DATE	VER
EXECUTED	USERADMIN	 THREE PHASE W22 MOTOR FRAME 160M IP55 TEFC				PREVIEW WDD				
CHECKED										
RELEASED										
REL DT		WMO	Jaragua do Sul	Product Engineering	SHEET	1	/	1		