

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :					
Product line : W22 IE1 Three-Phase		Product code : 11098382			
Frame : 250S/M Output : 55 kW Poles : 2 Frequency : 50 Hz Rated voltage : 380/660 V Rated current : 100/57.6 A L. R. Amperes : 670/386 A LRC : 6.7 No load current : 25.0/14.4 A Rated speed : 2955 rpm Slip : 1.50 % Rated torque : 18.1 kgfm Locked rotor torque : 200 % Breakdown torque : 240 % Insulation class : F Service factor : 1.00 Moment of inertia (J) : 0.3736 kgm ² Design : N		Locked rotor time : 21s (cold) 12s (hot) Temperature rise : 80 K Duty cycle : S1 Ambient temperature : -20°C to +40°C Altitude : 1000 m.a.s.l. Protection degree : IP55 Cooling method : IC411 - TEFC Mounting : B3T Rotation ¹ : Both (CW and CCW) Noise level ² : 75.0 dB(A) Starting method : Direct On Line Approx. weight ³ : 451 kg			
Output	50%	75%	100%	Foundation loads Max. traction : 218 kgf Max. compression : 669 kgf	
Efficiency (%)	92.3	92.9	92.5		
Power Factor	0.83	0.88	0.90		
		<u>Drive end</u> Bearing type : 6314 C3 Sealing : WSeal Lubrication interval : 5000 h Lubricant amount : 27 g Lubricant type : Mobil Polyrex EM	<u>Non drive end</u> 6314 C3 WSeal 5000 h 27 g		
Notes					
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.		These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in IEC 60034-1.			
Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by					
Date	21/11/2018			Page 1 / 4	Revision

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 4	
Date	21/11/2018				

TORQUE AND CURRENT VS SPEED CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IE1 Three-Phase

Product code : 11098382



Performance : 380/660 V 50 Hz 2P

Rated current : 100/57.6 A
LRC : 6.7
Rated torque : 18.1 kgfm
Locked rotor torque : 200 %
Breakdown torque : 240 %
Rated speed : 2955 rpm

Moment of inertia (J) : 0.3736 kgm²
Duty cycle : S1
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : N

Locked rotor time : 21s (cold) 12s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 4Revision		
Checked by				
Date	21/11/2018			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IE1 Three-Phase

Product code : 11098382




Performance : 380/660 V 50 Hz 2P


Rated current : 100/57.6 A
LRC : 6.7
Rated torque : 18.1 kgfm
Locked rotor torque : 200 %
Breakdown torque : 240 %
Rated speed : 2955 rpm

Moment of inertia (J) : 0.3736 kgm²
Duty cycle : S1
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : N


Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 4 / 4	Revision
Checked by					
Date	21/11/2018				



Without vertical jackscrews
Color RAL 5009
Painting plan 203A
Mounting B3T



55 kW 02 Poles 50 Hz A

ECM	LOC	SUMMARY OF MODIFICATIONS				EXECUTED	CHECKED	RELEASED	DATE	VER
EXECUTED	USERADMIN	 THREE PHASE W22 MOTOR FRAME 250S/M IP55 TEFC				PREVIEW WDD				
CHECKED										
RELEASED										
REL DT		WMO	Jaragua do Sul	Product Engineering	SHEET	1	/	1		